

**PIM 15 - PIA 15** Mechanical Tweezers or Pneumatic Tweezers model 15

**DESCRIPTION :**

- Light tweezers, easy to handle.

**PIM 15 :**

- Mechanical tweezers with one moving electrode for spot welding.
- Electrode driven by lever.
- Delivered with electrodes Ø 3 mm Cu Cr Cz.
- Force maxi. at electrodes 10 DaN.
- Various configurations available : straight output or 90° angle output.



PIM 15

**PIA 15 :**

- Pneumatic tweezers with one moving electrode for spot welding.
- Electrode driven by single stroke cylinder.
- Delivered with electrodes Ø 6 mm Cu Cr Cz.
- Welding start driven by an air temporized control unit (CTA).
- Adaptable to all of SOUDAX generators.

PIA 15



**DIMENSIONS**

- Length : 150 mm
- Height : 50 mm
- Width : 20 mm

**CABLES :**

- Length: 1.5 m
- Section : 35 mm<sup>2</sup>
- The cable can be equipped with an eyelet type connection or with a quick disconnect plug.

**Linked products**



**CC-AT**  
AIR DELAY CONTROL BOX



**GMF 5KA LS**  
Medium Frequency Generator  
5KA 2000Hz serial link

**Dedicated applications**

- Fabrication d'écran de protection thermique